



KAMMAK


Descaling Pumps & Flushing Compressors

PRATTIK 40[®]


Effective, Easy Cleaning for Heating Systems

The Kammak PRATTIK 40 descaling pump is designed for safe and easy removal of corrosion debris, sludge and scale from heating systems. It is a professional solution for cleaning heat exchangers, boilers, heating systems, water heaters and plastic injection moulding systems.


- High performance and flow rate
- Compact with ergonomic design
- Flow reverser
- Complete with easy-to-use hoses and fittings




40 lt tank capacity



Total weight
17,5 kg



Flow rate 260 l/min



Flow Reversal



KAMMAK

High performance
descaling pumps and
flushing compressors

Additional Features

- High flow rate for maximum cleaning
- Flow reversal
- Complete with hoses and fittings
- Rapid removal of system debris
- Ergonomic and compact design

Technical Specification

Pump Type	Vertical axis acid pump
Material of Construction	PE tank
Tank Capacity	40 lt
Dimensions (ØxH)	46 cm x 78cm
Weight	17,5 kg
Power Requirements	220-230V, 50Hz single phase motor, Europlug
Motor	650 W / 0.8 HP
Pressure	1 bar
Head	10 m
Flow Rate	260 l/min
Flow Rate [While the unit is connected to the system]	70 l/min - 1/2
Flow Rate [While the unit is connected to the system]	110 l/min - 3/4
Flow Rate [While the unit is connected to the system]	200 l/min - 1"
Hose	2x2,5m hoses
Max Temperature	60 °C
Degree of protection	Ip54
Connections/fittings	3/4"



KAMMAK Ltd Şti

Cataltepe Mh BESOB 6. Sok No:9/1 16450 Bursa, TURKEY

Tel: +90 546 223 28 98 www.kammakpumps.com