



KAMMAK





Descaling Pumps & Flushing Compressors

KPT-50®

Solar Filling Pump

The Kammak KPT-50 solar filling pump is designed for safe and easy filling and cleaning solar systems.

- High performance and flow rate
- Light weight and compact with ergonomic design
- Complete with easy-to-use hoses and fittings



KAMMAK

High performance
descaling pumps and
power flushing compressors

Additional Features

- High performance with 6 bar max pressure
- Built-in heater up to 60°C
- Complete with hoses and fittings
- Fine filter
- High flow rate for maximum cleaning
- Rapid removal of system debris
- Thermometer
- Manometer

Technical Specification

Material of Construction	Polyethylene tank and metal stand
Tank Capacity	16 litres
Dimensions	Height: 85cm/Width:35cm/Depth:40cm
Weight	18 kg
Power Requirements	220-230V, 50Hz Europlug
Motor	600W - 0.8 HP
Pressure	1-6 bar max pressure
Flow Rate	50 l/min
Hose	2x2,5m 16mm flow and return hoses
Physical Limitations	Maximum temperature range: 60 °C
Degree of protection	Ipx4
Connections/fittings	3/4"



KAMMAK Ltd Şti

Cataltepe Mh BESOB 6. Sok No:9/1 16450 Bursa, TURKEY

Tel: +90 546 223 28 98 www.kammakpumps.com